



multiLine

SURFACE AND PROFILE GRINDING MACHINE













ROBUST AND ECONOMICAL

- Large grinding width and length
- Grinding spindle with pre-loaded precision bearings
- High table load capacity
- Large variety of options available


INDIVIDUAL SOLUTION FOR SURFACE AND PROFILE GRINDING





multiLine - INDIVIDUAL SOLUTION FOR SURFACE AND PROFILE GRINDING

- Large grinding widths and lengths up to 6 meters as compact single column construction
- Additional vertical spindle as option
- Fast oscillation with short overtravel and precise positioning through linear motor table drive
- Wear free and quiet linear drive, table velocity up to 60 m/min
- High acceleration and deceleration of main axis
- Z-axis via traveling headstock allow large grinding lengths and stability
- Controls: xpressCube for surface grinding or Sinumerik 840 D for profile grinding
- Various dressing device options







Tilt dressing unit with 3 diamonds



Swivel dresser

TECHNICAL DATA						
multiLine	10	15	20	30	40	60
Drive system		•	KGT/HYD*	LIM*	LIM*	LIM*
Grinding width [mm]	700/900					
Grinding length [mm]	1000	1500	2000	3000	4000	6000
Distance spindle center to table [mm]	920/1120					
Spindle power [kW]	11/22/37					
Spindle cone [mm]	75/90					
Grinding wheel [mm]	400 × 60 × 127 500 × 150 × 203					

 $^{*\ \}textit{KGT} = \textit{Ball screw}; \textit{HYD} = \textit{Hydraulic cylinder}; \textit{LIM} = \textit{Linear motor}$

GET IN TOUCH WITH US TODAY

TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

ELB-SCHLIFF Werkzeugmaschinen GmbH

Phone: +49 6028 408 0 info@elb-schliff.de www.elb-schliff.de

08-2019

WE RESERVE THE RIGHT FOR TECHNICAL CHANGES!